

Electrical Lifting Trolley

ATH-3000

IDEAS, DESARROLLO
Y MEJORA, S.L.
www.idm-agrometal.com



ATH-3000 is the most complete lifting trolley available for greenhouses in the market.

Its hydraulic scissor elevation enables a 4.7 m. working height.

Main features:

- **Forward or reverse movement while pressing the pedal**, so hands are free to work. Smooth acceleration and braking.
- **Emergency stop on both chassis and control panel.**
- **All-terrain traction.** Special width wheels for sandy or hard grounds.
- **Clutch** for moving the trolley if battery is dead.
- Door opens inwards for safety. Self-closing door.
- **Telescopic steering-wheel and railing** to be adapted to each working height. Safety railing at 110 cm.
- Anti-skid working platform.
- **Battery charge indicator.**
- **Automatic battery charger.** Charge the batteries in the night-time and, when fully charged, they get automatically disconnected from the power supply.
- **2° inclinometer.**
- **Anti-rollover pothole.**

Engine and movements:

- Engine: 1CV
- Max. movement speed: 24 m / min.
- Average lifting speed: 4,7 m / min.
- Total lifting time: 32 s.

Dimensions and weight:

- Total length: 168 cm.
- Minimum width on wheels: 94 cm
- Minimum width on chassis: 75 cm
- Minimum width on platform: 60 cm
- Max. platform height: 2.95 m.
- Max. working height: 4,95 m.
- Weight: 485 kg.

