



Quality treatment:

- Homogeneous treatment.
- High manoeuvrability.
- Costs saving.

Main features:

- **Totally homogeneous treatment**, from first to last plant, covering all its height. Adaptable within crop features. Recommended by the European Crop Protection Association, ECPA.
- **High manoeuvrability**. Six-wheel drive and full 360° steering offers exceptional manoeuvrability and makes it much easier to drive efficiently into the greenhouse.
- Nozzles with **triple flow**. It allows selecting different flows depending on the application we want to make or even having different applications on different heights of the plant.
- Nozzle **height and wide** can be **regulated** according to the crop.
- Easy and **intuitive driving**, by means of an ergonomic joystick.
- Worker exposure to chemical reduced on a 75% according to ECPA tests.
- Around **30%** of phytosanitary-product **savings** in comparison to traditional methods.
- **Optimum sizes** for easy driving even in reduced spaces.
- 500 liters tank with **automatic hydro-loading device**.

Technical features:

- Engine: Lombardini-Kholer Diesel LDW 1003 26 CV.
- Spraying pump: Inmovilli P-63 pistons.
- Maximum spraying flow : 50 l to 40 bar.
- Hydrostatic transmission.
- Maximum speed:: 7km/h.

Weight and measures:

- Empty weight: 700 kg.
- Total length: 230 cm.
- Height without bars: 189 cm
- External width on tank: 75 cm
- External width on wheels: 85 cm

